

# Stereo VideoMic

X/Y Stereo Directional Video Condenser Microphone

**RØDE**<sup>®</sup>  
MICROPHONES

## Features

- Stereo X/Y Condenser Microphone
- Broadcast sound quality
- 9V battery powered
- Integrated shock mounting
- Two step High Pass Filter (Flat/80Hz)
- Rugged cast aluminium body
- Low noise circuitry
- Custom designed integrated windshield
- 3.5mm mini-jack output
- Integrated cold-shoe mount, 1/4" and 3/8" thread
- Designed and manufactured in Australia
- Full 10 year warranty\*



## Specifications

|                    |  |                     |  |
|--------------------|--|---------------------|--|
| Acoustic Principle | Pressure Gradient                        | Directional Pattern | Super-Cardioid                         |
| Frequency Range    | 40Hz ~ 20,000Hz<br>(selectable HPF@80Hz) | Sensitivity         | -38dB ±2dB re 1V/Pa @ 1kHz             |
| Nominal Impedance  | 200Ω                                     | Equivalent Noise    | 20dBA SPL<br>(A - weighted per IEC651) |
| Maximum Output     | +6.9dBu<br>(@ 1% THD into 1kΩ)           | Dynamic Range       | 115dB (per IEC651)                     |
| Maximum SPL        | 134dB (@ 1kHz, 1% THD into 1kΩ<br>load)  | Signal/Noise        | 74dB SPL<br>(A - weighted per IEC651)  |
| Power Req.         | 9V alkaline battery<br>(Current 7mA)     | Dimensions          | 170mmL x 102mmH x 65mmD                |
| Output Connection  | 3.5mm stereo mini-jack                   | Net Weight          | 176g                                   |

## Included Accessories

- DeadKitten windscreen

[www.rodemic.com](http://www.rodemic.com)

\*After online registration

Australia  
107 Carnarvon st, Silverwater NSW 2128 Australia  
Ph: +61 2 9648 5855    Fx: +61 2 9648 2455

USA  
6385 Rose Lane, Carpinteria CA 93013 USA  
Ph: +1 805 566 7777    Fx: +1 805 566 0071